



Aprimo Marketing Studio 9.0

Configuring the Integration Workbench

The product or products described in this book are licensed products of Teradata Corporation or its affiliates.

Aprimo and Teradata are registered trademarks of Teradata Corporation or its affiliates in the U.S. and other countries.

Other product and company names mentioned herein may be the trademarks of their respective owners.

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROVIDED ON AN "AS-IS" BASIS, WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR NON INFRINGEMENT. SOME JURISDICTIONS DO NOT ALLOW THE EXCLUSION OF IMPLIED WARRANTIES, SO THE ABOVE EXCLUSION MAY NOT APPLY TO YOU. IN NO EVENT WILL TERADATA CORPORATION BE LIABLE FOR ANY INDIRECT, DIRECT, SPECIAL, INCIDENTAL, OR CONSEQUENTIAL DAMAGES, INCLUDING LOST PROFITS OR LOST SAVINGS, EVEN IF EXPRESSLY ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

The information contained in this document may contain references or cross references to features, functions, products, or services that are not announced or available in your country. Such references do not imply that Teradata Corporation intends to announce such features, functions, products, or services in your country. Please consult your local Teradata Corporation representative for those features, functions, products, or services available in your country.

Information contained in this document may contain technical inaccuracies or typographical errors. Information may be changed or updated without notice. Teradata Corporation may also make improvements or changes in the products or services described in this information at any time without notice.

To maintain the quality of our products and services, we would like your comments on the accuracy, clarity, organization, and value of this document. Please e-mail: HelpFeedback@Teradata.com.

Any comments or materials (collectively referred to as "Feedback") sent to Teradata Corporation will be deemed non-confidential. Teradata Corporation will have no obligation of any kind with respect to Feedback and will be free to use, reproduce, disclose, exhibit, display, transform, create derivative works of, and distribute the Feedback and derivative works thereof without limitation on a royalty-free basis. Further, Teradata Corporation will be free to use any ideas, concepts, know-how, or techniques contained in such Feedback for any purpose whatsoever, including developing, manufacturing, or marketing products or services incorporating Feedback.

Copyright © 2013 Teradata Corporation

Introduction

If your organization purchased the Integration Workbench, complete these procedures to enable Aprimo Marketing Studio to communicate with external applications:

- Configuring the XML Publishing Service
- Setting the Integration Workbench Parameters

Note

The Integration Workbench does not support IPv6.

Configuring the XML Publishing Service

You configure the XML Publishing service on the server where the service will run. You also configure the service for each data source that might use the Integration Workbench.

1. Access the Configuration Manager with your Web browser.

Example

`http://ServerName/AprimoSysConfig/default.aspx`

Note

You must have administrator rights on the server where the Configuration Manager is installed.

2. On the navigation column, click **XML Publishing**.
3. Point to **Server**, and click the Integration Workbench server.

Note

You configured the Integration Workbench servers during the Aprimo Marketing Studio installation process.

Caution

You should turn off the debug function as soon as you have the data you need. Leaving the debug function enabled can negatively affect system performance.

4. Click **Edit**.
5. In the **Port** field, type the communication port number.

Note

We recommend port 5000. Make sure you select the same port configured in the Publishers module in Aprimo Tools.

6. Verify the **Queue Size** is **500**.
7. Verify the **Threads** field is set to **25**.
8. Do you need the server to write more detailed data to the event log for debugging purposes?
 - If no, continue with step 9.
 - If yes, in the **Debug** field, click **Yes**.

Caution

You should turn off the debug function as soon as you have the data you need. Leaving the debug function enabled can negatively affect system performance.

9. In the **Login** field for the appropriate data source, type the service user login name.

Caution

Once this service user is created, do not alter the service user's roles, rights, or passwords. This disables some integration features and may cause other unexpected results.

10. In the **Password** field, type the service user password.
11. Set the **Active** field to **Yes**.
12. Repeat steps 3 through 11 for the other data sources the Integration Workbench will use.
13. Click **Save**.

Setting the Integration Workbench Parameters

Use the Integration Workbench module in Aprimo Tools to set the Integration Workbench parameters.

1. Access Aprimo Marketing Studio with your Web browser.

Example

<http://ServerName/AprimoMarketing/default.aspx>

2. Type the login ID and password for the Admin user account.
3. In the **Data Source** field, click your data source.
4. In the **Domain** field, click your domain.
5. Click **Login**.
6. On the navigation column, click **Aprimo Tools**.

Tip

You will customize the navigation column later in the installation. After you customize the navigation column, you access Aprimo Tools from the System Administration navigation group.

7. On the navigation column, point to **Integration Workbench**, and click **Details**.
8. Click **Edit**.
9. Complete the fields.

Note

For more information, see the Integration Workbench Parameters table below or The Integration Workbench topic in the Help.

10. Click **Save**.

Integration Workbench Parameters

System Parameter	Description
Gateway URI	<p>Specifies the address of the Web service you want to use for inbound data transfers.</p> <p>Be sure the spelling and case of the URI you type matches the actual URI exactly, including http:// or https://.</p>
Event Publishing Status	<p>Determines whether the XML Publishing Service is running and is available to process data. When the status is Inactive, no subscriptions are processed and no data is sent from Aprimo Marketing Studio to client applications.</p> <p>The default value is Inactive.</p>
Interface Login Timeout	<p>Specifies the amount of time the client remains logged on to the XML Web service.</p> <p>You can enter a value between 0 and 999. When set to 0, the client will not time out.</p> <p>The default value is 0.</p>